

Cable attachment kit for on/off switch

Material no.: 1000002080 | Matchcode: EL AK ON OFF | EAN code: 4045294234898



- » universal cable kit for LED interior lighting in your LCV
- » enables on/off switch function
- » Cable length sufficient for vehicle of length L2
- » 10 Meter vehicle cables FLYY 2 x 0.75 mm²

Materials & Colour

Colour: Black

Dimensions

External dimensions: 320 x 210 x 25 mm

Technical details

Weight: 0,45 kg

Voltage in volts: 12-24 DC

Conformity

EMC Compliant: No

Accessories

	Material no.	Description	Matchcode	EAN code
--	--------------	-------------	-----------	----------



801014906	12 V on/off switch with orange indicator light	ZEASO	4045294165314
-----------	--	-------	---------------

Cable attachment kit for on/off switch

Material no.: 1000002080 | Matchcode: EL AK ON OFF | EAN code: 4045294234898

	Material no.	Description	Matchcode	EAN code
	6000002918	On/Off switch with round orange indicator light	EL WS ON/OFF OR	4045294431600
	6000000710	Two-way switch round on/on	EL WS ON/ON	4045294209810
	6000000711	Push-button switch round off/on	EL TS OFF/ON	4045294209827
	6000001305	Switch taperound D=20	EL AK S	4045294226282

Description

The cable attachment kit for on/off switch is a universal cable kit for providing an on/off switch for LED interior lighting with power and to regulate it. Cable length sufficient for vehicle of length L2.

The contents of a cable attachment kit for on/off switch in detail:

- 10 Meter vehicle cables FLYY 2 x 0.75 mm²
- 1 fuse holder ATO floor mounting
- 1 flat plug fuse 2A ATO grey
- 1 Ring connector for pins M6 0,5 – 1,5 mm² red
- 2 push on receptacles fully insulated 1.5 – 2.5 mm² 6.3 mm blue
- 3 through connectors 0.5 – 1.0 mm² red
- 2 push on receptacles fully insulated 0.5 – 1.0 mm² 4.8 mm blue

We reserve the right to make changes in the interest of technical progress, as well as correcting printing errors and mistakes. Pictures are similar, decorative material not included. With the publication of this data sheet, previous editions lose their validity. Version: 21.12.2023