

**LED-warning beacon yellow 10-30 V magnetic base**

Material no.: 6000002371 | Matchcode: LED KL G MAG | EAN code: 4045294269593



- » Magnetic foot with spiral cable
- » connection to cigarette lighter
- » no drilling necessary in the vehicle
- » Registration complying with ECE R65 & ECE R10-04
- » Operating voltage 10-30 VDC

**Dimensions**

External dimensions: 185 x 185 x 160 mm


**Technical details**

Weight: 1,39 kg  
IP Protection: 67  
Voltage in volts: 12  
24

**Conformity**




EMC Compliant: Yes  
ECE mark: E4 R65  
E4 10R-04

**Accessories**

	Material no.	Description	Matchcode	EAN code
	801009974	Extension cable 12 V	ZHSWV	4045294130640

## LED-warning beacon yellow 10-30 V magnetic base

Material no.: 6000002371 | Matchcode: LED KL G MAG | EAN code: 4045294269593

	Material no.	Description	Matchcode	EAN code
	801005397	12V Standard plug for internal use big	ZSD12AB2	4045294096731
	1000005394	Warning beacon magnetic holder for cross members	STS 2.0 KLM S QT	4045294531232
	1000002178	warning labels set for vehicles DIN 30710	WAMA FZS DIN 30710	4045294237202

### Description

This LED beacon is equipped with a magnetic base allowing it to be positioned as needed on the vehicle's roof. You can connect the light via the spiral cable with plug to the on-board socket/cigarette lighter (SAE J563) without the need for further cabling. The light can be operated with an operating voltage of 10-30 VDC. It also conforms to ECE R65 E04 006598 as well as ECE R10-04 and is extremely long-lasting thanks to the use of LED technology. The yellow flashing light is used to warn about hazards (see § 38 StVO). The light emits 120 double flashes per minute. It is ideal for operation outdoors, thanks to its IP67 protection class and temperature range of -40 to +70 °C. The height is 152 mm and the diameter is 183 mm. Refer also to §52 StVZO (Road traffic regulations) when operating beacons in public traffic. Note: The LED light is only intended for temporary use. It can only be positioned on flat, horizontal and normally painted surfaces on the (steel) vehicle roof. The recommended maximum speed with lights is 110 km/h.

### Successor

Material no.	Description	Matchcode	EAN code
6000015914	LED beacon yellow 12-24V magnetic socket	LED KLG MAG 12-24	4014599299734

We reserve the right to make changes in the interest of technical progress, as well as correcting printing errors and mistakes. Pictures are similar, decorative material not included. With the publication of this data sheet, previous editions lose their validity. Version: 29.02.2024