

LED beacon yellow 12-24V plug socket

Material no.: 6000015913 | Matchcode: LED KLG STSO 12-24 | EAN code: 4014599299710



- » Powerful LED warning beacon with ECE R65 approval
- » To fit plug socket type A Ø 24 mm according to DIN 72591
- » Simple to attach when required
- » Weather- and vibration-resistant (IPX5)
- » Operating voltage 12-24 V DC

Materials & Colour

Colour: Orange

Dimensions

External dimensions: 127 x 127 x 202 mm

Technical details

Weight: 0,89 kg
IP Protection: X5
Voltage in volts: 12-24 DC




Conformity

EMC Compliant: Yes
ECE mark: E6 65R-000036
E13 10R-04 12770

LED beacon yellow 12-24V plug socket

Material no.: 6000015913 | Matchcode: LED KLG STSO 12-24 | EAN code: 4014599299710

Accessories

	Material no.	Description	Matchcode	EAN code
	1000005392	Warning beacon plug base holder for side rails	STS 2.0 KLS S WA	4045294531218
	1000005393	Warning beacon plug base holder for cross members	STS 2.0 KLS S QT	4045294531225
	1000002178	warning labels set for vehicles DIN 30710	WAMA FZS DIN 30710	4045294237202

Description

This LED warning beacon is suitable for use with plug socket type A Ø 24 mm according to DIN 72591. The light can therefore be simply plugged into a fixed base on the vehicle or a telescopic mast when required. The yellow flashing light is used to warn against hazards (see also § 38 of the German Road Traffic Regulations StVO). The light can be operated with an operating voltage of 12-24 V DC. It complies with ECE R65 and ECE R10, and is extremely durable thanks to the LED technology used.

- » IPX5 tested for use outdoors
- » LED element: 10x 3 W LEDs
- » Average current draw: 1.7 A at 12.8 V DC / 0.88 A at 24 V DC
- » Max. current draw: 3.3 A at 12.8 V DC / 1.75 A at 24 V DC
- » Average output: 21 W
- » Max. power: 42 W
- » Recommended fuse: 5 A
- » Storage temperature: -40 °C to +75 °C
- » Operating temperature: -30 °C to +65 °C

Refer also to §52 of the German Road Traffic Registration Ordinance StVZO for the use of warning beacons on public roads.

We reserve the right to make changes in the interest of technical progress, as well as correcting printing errors and mistakes. Pictures are similar, decorative material not included. With the publication of this data sheet, previous editions lose their validity. Version: 18.03.2024